



## FIXT PERFORMANCE WOODSCREW

**SINGLE WIDE DEEP THREAD** –  
good pull out values

**DOUBLE RE-INFORCED  
COUNTERSUNK HEAD**  
with 4 self countersinking ribs

**POZIDRIVE DEEP RECESS**  
C1022 Carbon Steel – high strength,  
good ductility.

**8M YELLOW PASSIVATED  
ZINC PLATING**  
for superior corrosion resistance

**3:1 WAX LUBRICATION**  
for fast, low torque driving

**TYPE 17 SLASH POINT**  
for fast start

**CE/UKCA**  
certification from factory



## C2 TIMCO PREMIUM SCREW

**PRECISION PZ DRIVE RECESS**  
prevents 'cam-out', giving a precise and positive  
drive control on every screw.

**DOUBLE COUNTERSUNK**  
with Ribs helps improve countersinking, giving  
a smooth and flush finish whilst also preventing  
splitting and substrate damage.

**HELIX SHANK**  
helps remove debris and improve clamping.

**UNIQUE SYNTHETIC  
LUBRICATION**  
reduces insertion torque and increases rust  
protection up to 20x longer than a standard  
zinc plating.

**DUAL ANGLE THREAD**  
for ultimate performance and exceptionally  
high pull out resistance. (Partially threaded  
from 80mm)



## SPECTRE

**QUICK START TYPE 17 SLASH POINT**

**SAWTOOTH TO PREVENT SPLITTING**

**REAMER TO PREVENT JACKING**

**40 DEGREE DEEP SINGLE THREAD**

**FULLY THREADED UP TO 50MM**

**DOUBLE COUNTERSUNK**

**SURFACE HARDENED**

**SYNTHETIC LUBRICATION**



# What's the difference?

FEATURE	FIXT	C2	SPECTRE	CLASSIC	ULTIMATE	FORGEFAST
Pozi Drive	✓	✓	✓	✓	✓	✓
Double Countersunk Head with Ribs	✓	✓	✗	✗	✓	✓
Single Wide Deep Thread	✓	✓	✓	✓	✓	✓
High Strength C1022 Steel	✓	✓	✓	✓	✓	✓
Sawtooth Serrated Threads	✗	✗	✓	✗	✓	✓
Yellow Passivated Zinc Plating	8µm	5µm	5µm	5µm	5µm	Elementech
Lubrication for fast, Low Torque driving	✓	✓	✓	✓	✓	✓
Type 17 Slash Point for Fast Start	✓	✓	✓	✗	✗	✓
Driver Bit in each box	✓	✗	✗	✗	✓	✗
CE/UKCA Certified	✓	✓	✓	✓	✓	✓



## CLASSIC TIMCO MULTI- PURPOSE SCREW

**DOUBLE COUNTERSUNK**  
Reduces the likelihood of head shear and assists  
completion of countersinking.

**FULLY THREADED**  
up to and including 75mm

**PARTIALLY THREADED**  
thereafter (with 70mm thread length).

**MOLECULAR LUBRICATION**  
Patented lubrication, designed to enhance screw  
insertion time and provides greater resistance to  
corrosion.

**40° DEEP SINGLE THREAD**  
To provide a secure fixing with high pull out  
resistance.

**SURFACE HARDENED**  
Up to 750 HV to prevent torque shearing under load  
and a core hardness of up to 450 HV for improved  
ductility.

**TYPE 17 SINGLE SLASH**  
\*Single slash on 25mm. To reduce torque and the  
likelihood of the timber splitting when the screw is  
inserted close to the edge.



## ULTIMATE

**PSD® RECESS GIVING STICK-FIT®**

**HIGH-QUALITY STICK-FIT®**

**DRIVER BIT INCLUDED IN EVERY BOX**

**SELF-COUNTERSINKING  
HEAD WITH RIBS**

**CLASS-LEADING STRENGTH**

**SLOTTED SHANK FOR REDUCED  
WOOD SPLITTING**

**SHARP POINT AND PROMINENT  
THREAD FOR RAPID BITE**



## FORGE FAST

**DOUBLE CUTTING POINT**  
Reduces splitting and drive time, capable of  
penetrating 0.8mm steel.

**SERRATED CUTTING THREAD**  
reduces drive torque and improved pull-out for  
a firmer fix.

**ANTI-FRICTION THREAD**  
Prevents jacking and rotation of adjoining  
timbers whilst reducing splitting.

**REINFORCED  
COUNTERSUNK NECK**  
Improved holding power.

**6 ANGLED LUBES**  
For improved countersinking

For more information please contact [sales@fixtgp.co.uk](mailto:sales@fixtgp.co.uk)